

SLATE RANGE 2008

MINI STONEWOLD 63 BLACK

# Redland

Now available in a rich black finish, a flat concrete slate which can be laid at pitches as low as 17.5°



MINI STONEWOLD 63 BLACK



## SLATE RANGE 2008

### MINI STONEWOLD 63 BLACK



#### Authority

All concrete slates and tiles conform to BS EN 490:2004: Concrete roofing tiles and fittings for roof covering and wall cladding – Product specifications.

#### Roof System Guarantee

All of our products are designed and tested to work together. So not only is every product guaranteed weathertight, all the junctions between them are similarly guaranteed. If any Redland product fails during its first 15 years, we will not only replace it, we will also pay for the cost of labour and associated materials.

Besides guaranteeing the tiles and slates, this guarantee includes all our fittings and accessories. Indeed, the guarantee is so comprehensive that it is transferable to all future owners. A complete Redland roof is a completely guaranteed roof.



Now available in a rich black finish, a flat concrete slate which can be laid at pitches as low as 17.5°, for new build or re-roofing applications. Our most economical concrete slate with interlocking edges for simple construction.



Black  
63

u 1

u Painted 1 Through coloured

#### Technical Data

<b>Size (overall)</b>	418 x 334mm
<b>Minimum Pitch and Headlap</b>	
	17.5° at 100mm headlap
	22.5° at 75mm headlap
<small>(The minimum pitch is based on a maximum rafter length of 10 metres. For rafter lengths greater than this, please contact the Technical Solutions Hotline on 08708 702595)</small>	
<b>Maximum Pitch (subject to fixing specification)</b>	90°
<b>Maximum Headlap</b>	125mm
<b>Minimum Gauge/Batten Spacing</b>	293mm
<b>Maximum Gauge/Batten Spacing</b>	
below 22.5°	318mm
22.5° and over	343mm
<b>Hanging Length (approx.)</b>	397mm
<b>Cover</b>	
Linear cover of 1 slate	294mm
Covering capacity at maximum gauge <small>(all figures are net and do not allow for wastage)</small>	9.9 slates/m <sup>2</sup>
<b>Weight per 1000</b>	5.55 tonnes
at max. gauge approx.	53kg/m <sup>2</sup>
per pallet, including pallet (approx.)	1.21 tonnes
<b>Battens Required</b>	
at max. gauge	2.92m <sup>2</sup>
<b>Batten Size</b>	
Rafter centres up to 450mm	38 x 25mm
Rafter centres up to 600mm	50 x 25mm
<b>Nail Size for Slates</b>	50 x 3.35mm
<b>Number of Slates/Pallet</b>	216
Slates/Pack	36
Packs/Pallet	6

For further information please visit:

[www.redland.co.uk](http://www.redland.co.uk)

or contact Customer Service Hotline :

**08705 601000\***

email: [sales.redland@monier.com](mailto:sales.redland@monier.com)

\* When calling the Customer Service Hotline your telephone conversations may be recorded for training purposes.

#### Specification Support



**GUARANTEED ROOF SPECIFICATION**  
[www.redland.co.uk/specmaster](http://www.redland.co.uk/specmaster) or call 08708 702595



**CAD DRAWINGS**  
[www.redland.co.uk/designmaster](http://www.redland.co.uk/designmaster) or CD-ROM available



**PRODUCT VISUALISER**  
[www.redland.co.uk/viewmaster](http://www.redland.co.uk/viewmaster)



**SAMPLES**  
[www.redland.co.uk/samples](http://www.redland.co.uk/samples) or call 08705 601000