

ACCESSORY RANGE

RAPID FLASHING

# Redland



## Redland

15  
YEAR

ROOF SYSTEM  
GUARANTEE

# RAPID FLASHING



**MONIER**

## ACCESSORY RANGE

### RAPID FLASHING

**RAPID FLASHING** is a Lead Free, flexible, adhesive flashing designed to replace lead in most modern roofing applications. The product has many advantages over traditional lead flashings for those working in the construction industry, including the simple and quick installation process and non-toxic, lightweight material. **RAPID FLASHING** can be used for all wall abutments, chimneys and other rising parts of structures such as dormers.

#### Features

- Appearance of lead
- Lighter weight than lead and easy to use
- Can be moulded quickly and easily, without the need for special tools
- Manufactured from environmentally-friendly materials
- Insensitive to extremes of cold and heat (-40° to 100°C)
- UV resistant
- No scrap value means RAPID FLASHING is not at risk of theft
- Unrivalled speed of installation means flashing details can be completed up to twice as fast as standard practice
- Easy to achieve an outstanding flashing detail
- Self-fusing capabilities remove the need for welding and boss details
- Easy handling and storage
- Dirt resistant surface
- Low site waste due to ease of cutting and simple fixing
- In use on pitched roofs since 1991

#### Technical Data

Colours	Lead Grey		
Dimensions:	280mm x 5m	280mm x 10m	370mm x 5m
Weight (approx):	5 kgs	10 kgs	7 kgs
Stretch Factor			
Lengthwise:	approx. 50%		
Crosswise:	approx. 15%		
Temperature Stability:	-40°C to +100°C in accordance with DIN 52133		
UV-Resistance	in accordance with DIN 16726		
Fire Resistance	Class E		

#### Compatibility

- Compatible with all Redland tiles and slates
- Not suitable for use with the Top Edge Abutment Ventilation System
- Suitable for all pitches and plan angles
- Installation Guide must be followed for correct fitting

#### Environmental

- Non-toxic
- Unlike lead, copper and zinc, RAPID FLASHING produces no streaks on the roof.
- Less pollution than lead and copper; as the material does not dissolve in water
- No protective masks needed
- No toxic fumes as no welding is required
- None of the health and safety issues associated with lead

#### Storage Conditions

- Storage Temperature: +5 °C to +25 °C; for short times up to +40 °C (risk of butyl softening and difficulties to release protective foil)
- Prevent exposure to direct sunlight and moisture or rain
- Keep transport boxes and rolls covered and sheltered
- Rolls must be stored in upright position

#### Peace of Mind

- Guaranteed weathertight and secure for 15 years, when used in conjunction with the Redland range of tiles and slates
- Awarded British Board of Agrément Certification, certificate number 09/4622



For further information please visit:

[www.redland.co.uk](http://www.redland.co.uk)

or contact Customer Service Hotline:

**08705 601000\***

email: [sales.redland@monier.com](mailto:sales.redland@monier.com)

\*When calling the Customer Service Hotline your telephone conversations may be recorded for training purposes.

#### Specification Support



##### GUARANTEED ROOF SPECIFICATION

[www.redland.co.uk/specmaster](http://www.redland.co.uk/specmaster) or call 08708 702595



##### PRODUCT VISUALISER

[www.redland.co.uk/viewmaster](http://www.redland.co.uk/viewmaster)



##### SAMPLES

[www.redland.co.uk/samples](http://www.redland.co.uk/samples) or call 08705 601000