



Redland

Landmark Double Roman

50 Double Roman

Single Lap Interlocking Concrete Roof Tile




January-10 Issue 3
Issued by: Redland Technical Solutions

HOW TO DETERMINE THE CORRECT ZONAL FIXING SPECIFICATION FOR YOUR PROJECT (see Note)

1. Check you are using the right table. Projects involving counterbatens have a different set of tables.
2. For single lap slates/tiles identify the minimum headlap you want to lay the tile at.
3. Identify the rafter pitch of the roof to be tiled.
4. Identify which UK wind zone the project site is located in from the map i.e. Zone 1, 2 or 3 ?
5. Identify which Altitude band the project site is in. Check an OS map or see www.streetmap.co.uk.
6. Check the building height (to the ridge) and identify the correct row in the table.
7. Read off the appropriate fixing specification A, B, C, D, E, F etc. See Index below table for description.
8. See box below table for description of correct fixings to be used with product codes for ordering.

Note: The tables cannot be used for sites on slopes greater than 10% or within 6km of airports. If using an air-open underlay contact Technical Solutions Hotline to check suitability.

Map of UK Wind Zones



For the Channel Islands assume a wind speed of 24 m/s i.e. Zone 2

If the building lies on the junction of two wind speed zones use the higher wind speed zone when determining the fixing specification in accordance with the Zonal Method.

Map reproduced by kind permission of BRE Ltd.

Landmark Double Roman / 50 Double Roman - Tiles to be laid straight bond in even courses with tails aligned
TABLE OF ZONAL FIXING SPECIFICATIONS - For projects with counterbatens (above the underlay)

| Minimum Headlap | 75 mm | | 100 mm | | | | |
|--|---|----------|----------|-------------|----------|----------|---|
| Rafter Pitch | 22.5° - 34° | 35 - 44° | 45 - 54° | 17.5° - 34° | 35 - 44° | 45 - 54° | |
| ZONE 1 Maximum Building Height | Site Altitude: 0 - 100 m (above sea level) | | | | | | |
| | 5 m | D | D | E | D | D | E |
| | 10 m | D | D | E | D | D | E |
| | 15 m | D | D | E | D | D | E |
| | Site Altitude: 101 - 200 m (above sea level) | | | | | | |
| | 5 m | D | D | E | D | D | E |
| | 10 m | E | D | E | E | D | E |
| | 15 m | E | D | E | E | D | E |
| | Site Altitude: 201 - 300 m (above sea level) | | | | | | |
| | 5 m | D | D | E | E | D | E |
| | 10 m | E | D | E | E | D | E |
| | 15 m | E | D | E | E* | D | E |
| For Building Heights Greater than 15 m or Site Altitudes Greater than 300 m (above sea level) | | | | | | | |
| Contact Redland Technical Solutions, Tel. 08708 702595 | | | | | | | |
| ZONE 2 Maximum Building Height | Site Altitude: 0 - 100 m (above sea level) | | | | | | |
| | 5 m | D | D | E | D | D | E |
| | 10 m | E | D | E | E | D | E |
| | 15 m | E | D | E | E | D | E |
| | Site Altitude: 101 - 200 m (above sea level) | | | | | | |
| | 5 m | E | D | E | E | D | E |
| | 10 m | E | D | E | E | D | E |
| | 15 m | E* | D | E | E* | D | E |
| | Site Altitude: 201 - 300 m (above sea level) | | | | | | |
| | 5 m | E | D | E | E | D | E |
| | 10 m | PS | D | E | PS | D | E |
| | 15 m | PS | D | E | PS | D | E |
| For Building Heights Greater than 15 m or Site Altitudes Greater than 300 m (above sea level) | | | | | | | |
| Contact Redland Technical Solutions, Tel. 08708 702595 | | | | | | | |
| ZONE 3 Contact Redland Technical Solutions, Tel. 08708 702595 | | | | | | | |


* Minimum pitches in table are for through coloured tiles only. For granular finish tiles the minimum pitches are 30° (at 75 mm minimum headlap) and 22.5° (at 100 mm minimum headlap).

Index to Zonal Fixing Specifications

- A No fixings required
- B Each tile once nailed (right hand hole on flat tiles)
- C Each tile twice nailed (flat tiles only)
- D Each tile clipped
- E Each tile once nailed and clipped
- F Each tile twice nailed and clipped
- PS Each tile once screwed and clipped with Ring-Shanked Nail
- *

Description of Fixings to be used (incl. Product Codes)

- 60 x 3.35 mm Tile Nail (9333)
- 60 x 3.35 mm Ring-Shanked Tile Nail (9353)
- Tile Clip (9288) and Nails for Tile Clips (9333)
- Verge Clip (LH/RH) (9297/9121)
- Eave Clip (9287 (incl. nails))
- Left-Hand Cloaked Verge Eave Tile Clips (9179)
- 60 x 4 mm Countersunk Posidrive Screw (9358)



Tile Clip and Nails (9288 and 9333)



Verge Clip (LH/RH) (9297/9121)



Eave Clip and Nails (9287)

For all sales enquiries/orders contact our CUSTOMER SERVICE HOTLINE Tel. 08705 601000 / Fax. 08705 642742
For all technical enquiries contact our TECHNICAL SOLUTIONS HOTLINE Tel. 08708 702595 / Fax. 08708 702596