

## Norfolk Pantile



Single Lap Interlocking Concrete Roof Tile

January-10 Issue 3


Issued by: Redland Technical Solutions

### HOW TO DETERMINE THE CORRECT ZONAL FIXING SPECIFICATION FOR YOUR PROJECT (see Note)

1. Check you are using the right table. Projects involving counterbatens have a different set of tables.
2. For single lap slates/tiles identify the minimum headlap you want to lay the tile at.
3. Identify the rafter pitch of the roof to be tiled.
4. Identify which UK wind zone the project site is located in from the map i.e. Zone 1, 2 or 3 ?
5. Identify which Altitude band the project site is in. Check an OS map or see [www.streetmap.co.uk](http://www.streetmap.co.uk).
6. Check the building height (to the ridge) and identify the correct row in the table.
7. Read off the appropriate fixing specification A, B, C, D, E, F etc. See Index below table for description.
8. See box below table for description of correct fixings to be used with product codes for ordering.

Note: The tables cannot be used for sites on slopes greater than 10% or within 6km of airports. If using an air-open underlay contact Technical Solutions Hotline to check suitability.

### Map of UK Wind Zones



For the Channel Islands assume a wind speed of 24 m/s i.e. Zone 2

If the building lies on the junction of two wind speed zones use the higher wind speed zone when determining the fixing specification in accordance with the Zonal Method.

Map reproduced by kind permission of BRE Ltd.

Norfolk Pantile - Tiles to be laid straight bond in even courses with tails aligned						
TABLE OF ZONAL FIXING SPECIFICATIONS - For projects with counterbatens (above the underlay)						
Minimum Headlap	75 mm			100 mm		
Rafter Pitch	22.5 - 34°	35 - 44°	45 - 54°	17.5 - 34°	35 - 44°	45 - 54°
ZONE 1 Maximum Building Height	Site Altitude: 0 - 100 m (above sea level)					
	5 m	D	D	E	D	E
	10 m	D	D	E	D	E
	15 m	D	D	E	D	E
	Site Altitude: 101 - 200 m (above sea level)					
	5 m	D	D	E	D	E
	10 m	D	D	E	D	E
	15 m	D	D	E	D	E
	Site Altitude: 201 - 300 m (above sea level)					
	5 m	D	D	E	D	E
	10 m	D	D	E	D	E
	15 m	E	D	E	E	E
For Building Heights Greater than 15 m or Site Altitudes Greater than 300 m (above sea level) Contact Redland Technical Solutions, Tel. 08708 702595						
ZONE 2 Maximum Building Height	Site Altitude: 0 - 100 m (above sea level)					
	5 m	D	D	E	D	E
	10 m	D	D	E	D	E
	15 m	D	D	E	D	E
	Site Altitude: 101 - 200 m (above sea level)					
	5 m	D	D	E	D	E
	10 m	E	D	E	D	E
	15 m	E	D	E	D	E
	Site Altitude: 201 - 300 m (above sea level)					
	5 m	D	D	E	D	E
	10 m	E	D	E	E	E
	15 m	E	D	E	E	E
For Building Heights Greater than 15 m or Site Altitudes Greater than 300 m (above sea level) Contact Redland Technical Solutions, Tel. 08708 702595						
ZONE 3 Contact Redland Technical Solutions, Tel. 08708 702595						

### Index to Zonal Fixing Specifications




- A No fixings required
- B Each tile once nailed (right hand hole on flat tiles)
- C Each tile twice nailed (flat tiles only)
- D Each tile clipped
- E Each tile once nailed and clipped
- F Each tile twice nailed and clipped
- PS Proprietary System with Ring-Shanked Nail

### Description of Fixings to be used (incl. Product Codes)

- 45 x 3 mm Tile Nail (9334)
- Tile Clip (9177) and Nails for Tile Clips (9333)
- Verge Clip (LH/RH) (9148/9149)
- Eave Clip (9178) and Nails for Eaves Clips (9332)



Tile Clip and Nails (9177 and 9333)



Verge Clip (LH/RH) (9148/9149)



Eave Clip and Nails (9178 and 9332)